



# SP 2200 EI

Posizionatore a tavola rotante portata 2200 Kg. Rotazione motore con tecnologia ad inverter (I), riduttore a vite senza fine e ralla a sfere inclinazione con motore elettrico (E)

Turntable type positioner maximum load 2200 Kg. Motor rotation by inverter technology (I), motor through worm gear and ball slewing ring. Tilt: with electric motor (E)

Positionneur à table rotative portée 2200 Kg. Rotation avec moteur commandée par onduleur (I) , réducteur à vis sans fin et butée à billes. Inclinaison avec moteur électrique (E)

Drehtisch-Positionervorrichtungen Tragkraft 2200 Kg. Motorrotation durch Invertertechnologie (I), Endlos-schneckenuntersetzung und Kugelscheibe. Schwenkung mit Elektromotor (E).

Posicionadores de mesa giratoria portal 2200 Kg. Rotación con motor a tecnología de inverter (I), reductor de tornillo sin fin y rangua de bolas. Inclinaición con motor electrico (E)



SP 2200 EI
Q kg = 2200
Mt daNm = 220
Mf daNm = 665
D mm = 1400
H1 mm = 890
H2 mm = 1010
C mm = 125
L mm = 2114
W mm = 1380
Rpm = 0.07-0.7
Sec. = 85
Volt. = 3x380
Volt. = 24
LxWxH2 mm = 2114x1380x1010
Kg = 1650

ITEM	DESCRIPTION	PRICE EURO
SP 2200-EI	Turntable manual tilt. With pedal	21470.00
SP/SOR	Stop at 360°; adjustable overwelding function and auto return to “ 0”	1550.00
BPT300 M	Pneumatically actuated torch arm for Mig welding	2945.00
BPT300 T	Pneumatically actuated torch arm for Tig welding	3705.00
SP/PMA	Single pedal control (start-stop) with mt.5 (197” ) connection cable	228.00
SP/TMA	Start-stop control with botton and 5 mt. (197” ) connection cable	342.00
SP/TTA	Table delayed start device for TIG welding	988.00
SP/VL	Display LCD	608.00
SP/GR1	1-way rotating coupling for air or gas	551.00
SP/GR2	2-way rotating coupling for water	646.00
SP/SCH	Hi-frequency shielding	570.00

#### Packaging

Plants are usually supplied protected by a film, wooden crates are available on request with surcharge: 70 CHF NET