



SPS 150S HC 200

Posizionatore a tavola rotante portata 150 Kg. Rotazione con motore auto-frenante a corrente continua, riduttore a vite senza fine e ralla a sfere. Inclinazione manuale con foro passante Ø 200 mm.

Turntable type positioner maximum load 150 Kg. Slewing by DC selfbraking motor through worm and ball slewing ring. Tilt: manual. Hollow center Ø 200 mm.

Positionneur à table rotative portée 150 Kg. Rotation avec moteur auto-entretenu à courant continu, réducteur à vis sans fin et butée à billes. Inclinaison manuelle Avec trou central sur la table Ø 200 mm.

Drehtisch-Positionervorrichtungen Tragkraft 150 Kg. Rotation mit selbstbremsenden Gleichstrommotor, endlosschneckenuntersetzung und Kugelscheibe. Schwenkung manuell. Mit hohlwelle in Tisch Ø 200 mm.

Posicionadores de mesa giratoria portal 150 Kg. Rotación or motor freno de corriente continua, reductor de tornillo sin fin y rangua de bolas. Inclinaçión manual. Con agujero central en la mesa Ø 200 mm .



SPS 150S HC 200
A =
B =
C =
F diam mm =
E =
D =
H =
Volt =
RPM =
P1 Kg =
P2 Kg =
Mf Kgm =
P3 Kg =
P4 Kg =
Mt Kgm =
PESO Kg/Weight =

ITEM	DESCRIPTION	PRICE CHF
SPS 150 S HC 200	Turntable positioner for bench use. Manual tilt. Hollow center diameter 200 mm	12350.00
BPT 300 M	Pneumatically actuated torch arm for MIG welding	2945.00
BPT 300 T	Pneumatically actuated torch arm for TIG welding	3705.00

ACCESSORIES

SPS/TT	Table delayed start device for TIG welding	798.00
SPS/SCH	Hi-frequency shielding	570.00
SPS/VL	Display LCD	608.00
SPS/TF	Crater filler device for TIG/MIG welding	912.00

LEGEND

SPS	Turntable positioner standard version
SPS ... S	Turntable positioner with overwelding function and single control for slewing and welding power source start
SPS ... HC	Turntable positioner with 100 mm. hollow centre turntable
SPS ... S HC	Turntable positioner with overwelding function, single control for slewing and welding power source start and hollow centre turntable

Packaging : wooden crate surcharge CHF 42.00 net