



# SPS 75 HC


Posizionatore a tavola rotante portata 70 Kg. Rotazione con motore auto frenante a corrente continua, riduttore a vite senza fine e ralla a sfere. Inclinazione manuale , foro passante Ø 100 mm.

Turntable type positioner maximum load 70 Kg. Slewing by DC selfbraking motor through worm and ball slewing ring. Tilt: manual

Positionneur à table rotative portée 70 Kg. Rotation avec moteur auto-maintenu à courant continu, réducteur à vis sans fin et butée à billes. Inclinaison manuelle.

Drehtisch-Positionervorrichtungen Tragkraft 70 Kg. Rotation mit selbstbremsenden Gleichstrommotor, endlosschneckenuntersetzung und Kugelscheibe. Schwenkung manuell .

Posicionadores de mesa giratoria portal 70 Kg. Rotación por motor freno de corriente continua, reductor de tornillo sin fin y rangua de olas. Inclinación manual.



SPS 75 HC
A = 600
B = 500
C = 330
F diam mm = 500
E = 710
D = 70
H = 910
Volt = 220
RPM = 0,5 - 12
P1 Kg = 70
P2 Kg = 35
Mf Kgm = 7
P3 Kg = 48
P4 Kg = 30
Mt Kgm = 5
PESO Kg/Weight = 105

ITEM	DESCRIPTION	PRICE CHF
SPS 75 HC	Turntable positioner for bench use. Manual tilt. Max acceptable load 70Kg (154 Lbs)	5130.00

ACCESSORIES

SPS/TT	Table delayed start device for TIG welding	798.00
SPS/SCH	Hi-frequency shielding	570.00
SPS/VL	Display LCD	608.00
SP/TF	Crater filler device for TIG/WIG welding	912.00

LEGEND

SPS	Turntable positioner, standard version
SPS ... S	Turntable positioner with overwelding function and single control for slewing and welding power source start
SPS ... HC	Turntable positioner with 100 mm. hollow centre turntable
SPS ... S HC	Turntable positioner with overwelding function, single control for slewing & welding power source start and hollow centre turntable

Packaging : wooden crate surcharge CHF 42.00 net